

Microtek NDT/RT Digitizing System MII-1000 LC

Microtek NDT/RT Film Digitizing System is an all-in-one imaging solution developed exclusively for radiographic inspection industry. It easily transfers the industrial X-Ray film into digital image for storage and management and makes it convenient to view and share for the professionals. It is a cost-effective way to step into industrial X-Ray film digitizing management.

MII-1000 LC

Combined with years of image professional experiences, MII-1000 LC, an industrial film digitizer, is specifically designed and built for the use of industrial X-Ray film scanning. Its sheet-fed design, hard metal body with a net weight 9 kg, is equal to a printer size which fits in use in a limit space.

In addition, the MII-1000 LC lets you easily scan various sizes of industrial X-Ray film up to 14" x 200", which offers more flexibility in physical records digitizing. Simply using exclusive film holders, the MII-1000 LC can automatically crop the scan frame to fit the size of original film, making your work more efficiently. Besides, two optional accessories, automatic film feeder and multi-channel tray, make scanning of multiple-sheet of film at a time more conveniently, effectively and time-saving.

Besides, the MII-1000 LC 2400 dpi resolution, 16-bit grayscale, and 4.7 maximum optical density (Dmax), allow it to capture a wide range of grayscale displaying tones from light to dark gray. Applying with revolutionary technology, the MII-1000 LC optimizes the image with low noise and enlarge signal of the dark area of the film, producing a high-quality and better visible image. It satisfies a demand of high quality in radiographic inspection industry.

Furthermore, the system contains powerful image management software, MiiNDT, which is tailor-made for Microtek industry film digitizers. It has a state of the art user interface and offers rich functionality for easy to use, allowing recording the data related to the film in digital format. It features many image adjustment and measurement tools to capture, inquire, and measure images. Most important of all, MiiNDT supports 100% real size prints of original images that is very convenient for engineers to find the defect part immediately at operating site. It is a time-efficient and effective solution for industry image management.

Features

Multi-Channel Tray Up to 3 pics in one scan

- Warm-up free with energy-saving LED light source
- Optional 15-sheet automatic film feeder and 3-sheet multi-channel tray
- 2400 dpi resolution, 4.7 maximum optical density, and 16-bit grayscale capability
- Maximum scan area up to 14" x 200" covers all standard film formats
- \cdot Exclusive industrial film holders 8.5" x 4.5" and 12" x 3 1/3"
- · Improves the quality of the displayed image
- Provides powerful image management, including image archiving, inquiry, measurement tools, annotation, reporting, viewing, CD burning, transferring, converting to DICONDE format, etc.
- Supports DCM, BMP, JPEG, and TIFF formats
- Supports JPEG 2000 lossless and lossy data compression formats
- Conform to ASTM international standard & DICONDE format
- Cost-effective, all-in-one imaging solution for NDT/RT



User Friendly, Easy Access

Microtek NDT/RT Film Digitizing System is able to emphasize the details in shadows, increasing clarity on demand and faithfully present the nature of the originals. Microtek NDT/RT Film Digitizing System enables you to manage the industrial X-Ray films efficiently. Combining the use of MiiNDT and MII-1000, speedy image capture, image data management, and off-site viewing are just easier than ever.

With just a simple and fast connection, you are able to transfer physical data into digital format. The digital data format includes inspection date, project numbers, target numbers, and other related information, is qualified for ASTM standard and DICONDE format. In addition, MiiNDT provides functions for image annotation, reporting, CD-burning, transmitting, and converting to DICONDE format. It makes NDT/RT images easier to archive, review, and share.



Superb Ability to Differentiate Layers of Shadows

Microtek NDT/RT Film Digitizing System is able to emphasize the details in shadows, increasing clarity on demand and faithfully present the nature of the originals.



ShangHai Microtek Technology Co., ltd Building.35 NO.680 GuiPing Road, Shanghai200233, P.R. China, Tel: +86-021-64856614 http://www.microtek.com.cn

© 2018 Microtek, Microtek, ScanMaker, ArtixScan, and ScanWizard are trademarks or registered trademarks of Microtek International, Inc. All other brands, product names and logos herein are trademarks or registered trademarks of their respective holders. Specifications, software bundles and accessories are subject to change without notice. Delivery, of technical support services subject to change without notice. Not responsible for typographical errors. © 2018 1238P Publishing. 2018 1209

Specifications



Туре	Sheet-fed film digitizer
Image Sensor	CCD
Lamp Source	LED
Scanning Method	Grayscale in single scanning pass
Bit Depth	8-bit, 16-bit grayscale
Resolution	2400 dpi (11 μm)
Optical Density	4.7 Dmax
Dynamic Range	0.5D ~ 4.5D based on ISO 14096, DS 10.0
Scanning Area	14" x 200" (355.6 mm x 5080 mm)
Film Size	Min: 2.5" x 2.5″ (63.5 mm x 63.5 mm) Max: 14" x 200" (355.6 mm x 5080 mm)
Interface	Hi-Speed USB (USB 2.0)
Film Holders	8.5" x 4.5", 12" x 3 1/3"
Dimensions (L x W x H)	12.9" x 18.6" x 8.8" (329 mm x 474 mm x 224 mm)
Weight	44.53 lbs. (20.2 kg)
Power Supply	AC 100V to 240V, 50-60 Hz, 1.5A Max (Input)
Power Consumption	300 W (Max)
Certifications	CE, FCC, BSMI, ETL, CCC, RoHS

System Requirements

DVD-ROM drive (for installing software)

- 4GB RAM or above
- Pentium IV PC or higher with Hi-Speed USB (USB 2.0) port
- Microsoft Windows XP / 7 / 8 /10

Inbox Contents

- Digitizer unit with film holders
- Power cord
- High-Speed USB 2.0 cable
- CD (includes scanner scanning driver)
- Manual
- Software security dongle



